

PFC300 Series

Tub & Tile Caulk



DESCRIPTION

PROFLO TUB & TILE is an easy to apply, flexible adhesive designed to provide a wide range of uses on most surfaces. It is based on a specially modified co-polymer latex, which is compounded with selective additives, pigments and adhesion aids, to provide a fast curing, durable mildew resistant adhesive caulk.

MODEL NUMBERS

PFC300WHT 10.1 oz cartridge, White
PFC301WHT 5.5 oz squeeze tube, White

PROMINENT FEATURES

- May be used as an adhesive as well as a caulk.
- Excellent for Kitchen and Bath applications.
- Dries bright white
- Mildew Resistant
- This product is vacuumized to remove all microscopic air to ensure the maximum in durability and gunnability.

BASIC USES

PROFLO Tub & Tile is particularly suitable for interior or exterior applications such as boats, tubs, sinks, cabinets, shower and tiles. It is not recommended for use on mirrors, aquariums or under the waterline. It bonds tenaciously to metal, glass, wood, ceramic tile, Formica and other common surfaces and may be used as an adhesive as well as a caulk.

COVERAGE

A 1/8" x 1/4" bead will yield approximately 50 linear feet of sealant per 10.1 oz cartridge. A 1/8" x 1/4" bead will yield approximately 27 linear feet of sealant per 5.5 oz squeeze tube. When using, do not keep in direct sunlight for prolonged periods.



SURFACE PREPARATION

Surface must be clean, dry and free from dirt, dust, grease, oil, mildew, wax, loose paint and old caulking material. Prime bare surfaces before caulking. Apply only when sealant and surface temperatures are above 50°F (10°C).

To remove mildew, scrub with a solution of 3 heaping teaspoonsful of Trisodium Phosphate (TSP), 1 quart of Hypochlorite Household Bleach and 3 quarts of warm water. (Wear protective goggles and waterproof gloves.) Rinse thoroughly and allow to dry. Non-structural shrinkage cracks (larger than 1/16" wide) and non-structural movement cracks (larger than 1/16" and up to 1/4" wide) must be treated and repaired accordingly.

METHOD OF APPLICATION

1. Cut nozzle at a 45° angle to desired thickness to bead. Apply with a standard caulking gun. Use a steady pressure to completely fill joints.
2. For a neat appearance, smooth bead with a moistened finger, brush or cloth.
3. For best results, cured beads should be between 1/8"-1/2" wide and 1/8-1/4" deep. A 1/8"x1/4" bead will yield approximately 51 linear feet of sealant per cartridge. Important: Use Backer Rod for cracks and seams deeper than 1/4".
4. Remove excess material before cure with a moistened cloth. Clean up tools with water.
5. May be painted over with latex or oil based paints when dry (generally within 4 to 6 hours, depending on climatic conditions). Larger bead may require longer drying times.

CLEAN-UP

Clean all equipment immediately after use with warm, soapy water.

STORAGE


Do not stock containers below 40°F. Warm to above 50°F prior to use. Storage in direct sunlight or excessive heat will reduce working time and shelf life.

LIMITATIONS

- Do not use for structural repairs.
- Do not use below grade or under water.
- Not recommended for food surfaces.
- Application should be made when temperature of air and surface is 50°F (10°C.) or above for a 24 hour period.
- If rain or threatening weather is expected within 8 hours, delay application until dry conditions exist.
- Allow new concrete to cure for 30 days before applying. After 30 days, test for alkali presence.
- Do not apply if pH is above 10.
- Do not apply if relative humidity is above 90%.
- Do not freeze.

LIMITED WARRANTY

If, when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and this used cartridge. This limited warranty applies only to residential use and damages, including consequential damage and other remedies, are excluded. No other warranties apply, including fitness for particular purpose.



CAUTION!
DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
KEEP FROM FREEZING.

PFC300 Series

Tub & Tile Caulk



| Typical Properties - Supplied | Test method | PFC300 |
|--|----------------------|---|
| % solids by weight | Lab value +/- 1% | 73.8 |
| % solids by volume | Lab value | 63 |
| Viscosity | Semco - 1/8" orifice | 9 |
| Specific Gravity (water = 1) | | 1.36 |
| Physical Form | Observation | Smooth Paste |
| Color | Observation | |
| Odor | Subjective | Trace Ammonia |
| Tack free time in minutes | ASTM D2377 | <60 min. |
| Tooling time | Lab value | 10 min. |
| Paint Over Time | | 2 hrs |
| Full Cure Time | | 24 hrs |
| Freeze/Thaw Stability | C731 | 5 cycles |
| Temperature Application Range | | >40°F (5°C) |
| Volatile Organic Content Weight % | Calculated | CARB Non-chem curing (n.a.) < 1.5 wt. % |
| VOC excl. H2O (G/L): | | < 38 |
| Flash Point | Estimated | > 62 °C; 144 °F |
| Shelf life | | 24 month |
| Typical Properties - Cured | | |
| Joint Movement Capability | N/A | N/A |
| Temperature Service Range (after cure) | | 0°C to 82°C |
| Slump inch. | ASTM D2202 | 0.1 |
| Durometer hardness | ASTM D2240 | 50 |
| Paintable | | Latex & Oil Based |
| Cleanup | | Water |



| | |
|-----------------|--------------|
| ALT CODE | (OLD) |
| PFC300WHT | (PFL007) |
| PFC301WHT | (PFL009) |

CAUTION!
DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
KEEP FROM FREEZING.



MATERIAL SAFETY DATA SHEET

Version: 1.20
06/03/2014

PFC300WHT ACRYLIC CAULK

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer Name: Momentive Performance Materials - Daytona
703 South Street
New Smyrna Beach FL 32168

Revised: 01/09/2013

Prepared by Product Regulatory Compliance
CHEMTREC 1-800-424-9300

MSDS Contact 1-888-443-9466
Information 4information@momentive.com

Chemical Family/Use: Sealant

Formula: Mixture

HMIS

Health: 1 Flammability: 0 Reactivity: 0

NFPA

Health: 1 Flammability: 0 Reactivity: 0

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! Harmful if inhaled, absorbed through skin, or swallowed. May cause skin, eye, and respiratory tract irritation. Do not breathe vapors.

Form: Solid

Form: White

Odor: Ammonia.

POTENTIAL HEALTH EFFECTS

INGESTION

Harmful if swallowed. Irritation of the mouth, throat, and stomach. May cause reproductive effects based on results of animal studies.

SKIN

May be absorbed through the skin and contribute to the symptoms listed under "Ingestion".

INHALATION

May cause irritation to the mucous membranes and upper respiratory tract. High concentrations of vapors may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Avoid inhalation of vapors and spray mists.

EYES

Contact can cause severe irritation and conjunctivitis (redness and swelling).

MATERIAL SAFETY DATA SHEET

Version: 1.20
06/03/2014

PFC300WHT ACRYLIC CAULK

MEDICAL CONDITIONS AGGRAVATED

Persons with pre-existing respiratory tract, skin, lung (such as asthma), and kidney disorders may be aggravated by exposure to this product.

SUBCHRONIC (TARGET ORGAN)

Respiratory System; Kidney

CHRONIC EFFECTS / CARCINOGENICITY

This product contains stoddard solvent or mineral spirits. Chronic and repeated overexposure may result in adverse liver and kidney effects, bone marrow hyperplasia, and intracerebral hemorrhage.

ROUTES OF EXPOSURE

Dermal; Eye

3. COMPOSITION/INFORMATION ON INGREDIENTS

| <u>PRODUCT COMPOSITION</u> | <u>CAS-No.</u> | <u>WGT. %</u> |
|--|----------------|---------------|
| <u>A. HAZARDOUS</u> | | |
| Butyl benzyl phthalate | 85-68-7 | 5 - 10 % |
| DISTILLATES, PETROLEUM,HYDROTREATED | 64742-47-8 | 0.1 - 1 % |
| <u>B. NON-HAZARDOUS</u> | | |
| CALCIUM CARBONATE | 1317-65-3 | 30 - 60 % |
| Water | 7732-18-5 | 10 - 30 % |
| Vendor Trade Secret Acrylic polymer | - | 10 - 30 % |
| 2-Propenoic acid, Butyl ester,-Polymer with Ethenyl Acetate | 25067-01-0 | 1 - 5 % |
| QUARTZ | 14808-60-7 | 0.1 - 1 % |

4. FIRST AID MEASURES

INGESTION

Do NOT induce vomiting. Get medical attention immediately. Do not give victim anything to drink if

MATERIAL SAFETY DATA SHEET

Version: 1.20
06/03/2014

PFC300WHT ACRYLIC CAULK

he is unconscious.

SKIN

Flush skin with large amounts of water for at least 15 minutes until no evidence of chemical remains. Wash with soap and water.

INHALATION

Move to fresh air.

EYES

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

| | |
|------------------------------|-------------------|
| FLASH POINT: | > 93.3 °C; 200 °F |
| METHOD | Estimated |
| IGNITION TEMPERATURE: | Not applicable |
| FLAMMABLE LIMITS LEL: | Not applicable |
| FLAMMABLE LIMITS UEL: | Not applicable |

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable. None

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

MATERIAL SAFETY DATA SHEET

Version: 1.20
06/03/2014

PFC300WHT ACRYLIC CAULK

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Use only in well-ventilated areas. Avoid accidental ingestion of this material. Wash hands and face before eating, drinking, smoking, using toilet facilities, or applying cosmetics.

Keep container closed. Keep out of reach of children.

STORAGE

Keep away from heat, sparks and open flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Safety shower.; Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Neoprene

EYE AND FACE PROTECTION

Monogoggles

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

| <u>Component</u> | <u>CAS-No.</u> | <u>Source</u> | <u>Value</u> |
|------------------------|----------------|-----------------|--------------------|
| Butyl benzyl phthalate | 85-68-7 | Z_INTL_OEL, TWA | No data available. |
| Butyl benzyl phthalate | 85-68-7 | ACGIH, TWA | No data available. |

MATERIAL SAFETY DATA SHEET

Version: 1.20
06/03/2014

PFC300WHT ACRYLIC CAULK

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--------------------|
| BOILING POINT (°C): | Not applicable |
| VAPOR PRESSURE (20 C) (MM HG): | Not applicable |
| VAPOR DENSITY (AIR=1): | Not applicable |
| FREEZING POINT: | Not applicable |
| PHYSICAL STATE: | Solid |
| ODOR: | Ammonia. |
| Color: | White |
| SPECIFIC GRAVITY: | No data available. |
| DENSITY: | No data available. |
| ACID / ALKALINITY (MEQ/G): | Not applicable |
| pH: | No data available. |
| SOLUBILITY IN WATER (20 C): | No data available. |
| SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT): | No data available. |
| VOLATILE ORGANIC CONTENT: | 0.35 %(m) |
| VOC EXCL. H2O & EXEMPTS (G/L): | 36.98 g/l |

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION.

Hazardous polymerisation does not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide; Toxic fumes.

INCOMPATIBLE MATERIALS

None known.

CONDITIONS TO AVOID

No data available.

MATERIAL SAFETY DATA SHEET

Version: 1.20
06/03/2014

PFC300WHT ACRYLIC CAULK

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: No data available.

ACUTE DERMAL

Remarks: No data available.

ACUTE INHALATION

Remarks: No data available.

OTHER

Contains ethylene glycol which causes birth defects in laboratory animals.

SENSITIZATION

No data available.

SKIN IRRITATION.

No data available.

EYE IRRITATION

No data available.

MUTAGENICITY

No data available.

OTHER EFFECTS OF OVEREXPOSURE

This product contains butyl benzyl phthalate. Adverse reproductive effects have been reported in animals exposed to butyl benzyl phthalate through chronic feeding studies. Additionally, chronically fed rats exhibited leukemia and lymphomas, including Hodgkin's disease.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

Ecotoxicological data for this product is not available.

DISTRIBUTION

No data available.

CHEMICAL FATE

No data available.

MATERIAL SAFETY DATA SHEET

Version: 1.20
06/03/2014

PFC300WHT ACRYLIC CAULK

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

| | | |
|--|----------------------|-------------------|
| Australia Inventory of Chemical Substances (AICS) | n (Negative listing) | |
| EU list of existing chemical substances | n (Negative listing) | |
| Japan Inventory of Existing & New Chemical Substances (ENCS) | n (Negative listing) | |
| China Inventory of Existing Chemical Substances | n (Negative listing) | |
| Korea Existing Chemicals Inventory (KECI) | n (Negative listing) | |
| Canada DSL Inventory | y (positive listing) | |
| Canada NDSL Inventory | n (Negative listing) | |
| Philippines Inventory of Chemicals and Chemical Substances (PICCS) | n (Negative listing) | |
| TSCA list | y (positive listing) | On TSCA Inventory |

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

SARA (311,312) HAZARD CLASS

Acute Health Hazard; Chronic Health Hazard

SARA (313) CHEMICALS

75-21-8, Ethylene Oxide. 50-00-0, Formaldehyde. 79-06-1, Acrylamide. 108-05-4, Vinyl Acetate. 107-13-1, Acrylonitrile.

CALIFORNIA PROPOSITION 65

Warning! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

MATERIAL SAFETY DATA SHEET

Version: 1.20
06/03/2014

PFC300WHT ACRYLIC CAULK

Canadian Regulatory Information

WHMIS CLASSIFICATION

D2A - Very Toxic Material Causing Other Toxic Effects

D2B - Toxic Material Causing Other Toxic Effects

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

,C = ceiling limit NEGL = negligible
EST = estimated NF = none found
NA = not applicable UNKN = unknown
NE = none established REC = recommended
ND = none determined V = recommended by vendor
SKN = skin TS = trade secret
R = recommended MST = mist
NT = not tested STEL = short term exposure limit
ppm = parts per million ppb = parts per billion

By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).



**PFC301WHT
Acrylic Caulk**

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Daytona Plant
703 South Street
New Smyrna Beach FL 32168

Revised: 03/25/2011

Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Sealant
Formula: Mixture

HMIS

Flammability: 0 Reactivity: 0 Health: 1

NFPA

Flammability: 0 Reactivity: 0 Health: 1

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! Harmful if swallowed, inhaled, or absorbed through the skin. May cause skin, eye, and respiratory tract irritation. Do not inhale vapors.

Form: Solid **Color:** White

POTENTIAL HEALTH EFFECTS

INGESTION

Harmful if swallowed. Irritation of the mouth, throat, and stomach. May cause irritation of the gastrointestinal tract. May cause reproductive effects based on results of animal studies.

SKIN

May be absorbed through the skin and contribute to the symptoms listed under "Ingestion". Can cause irritation and reddening of the skin.

INHALATION

High concentrations of vapors may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Can irritate mucous membranes and respiratory tract with coughing and shortness of breath. Avoid inhalation of vapors and spray mists.

EYES

Contact can cause severe irritation and conjunctivitis (redness and swelling).

MEDICAL CONDITIONS AGGRAVATED

Pre-existing skin or respiratory diseases. Kidney disorders

Material Safety Data Sheet

Version: 1.1
06/03/2014

PFC301WHT Acrylic Caulk

SUBCHRONIC (TARGET ORGAN)

Respiratory System; Kidney

CHRONIC EFFECTS / CARCINOGENICITY

This product contains stoddard solvent or mineral spirits. Chronic and repeated overexposure may result in adverse liver and kidney effects, bone marrow hyperplasia, and intracerebral hemorrhage.

ROUTES OF EXPOSURE

Dermal; Eye

3. COMPOSITION/INFORMATION ON INGREDIENTS

| <u>PRODUCT COMPOSITION</u> | <u>CAS REG NO.</u> | <u>WGT. %</u> |
|---|--------------------|---------------|
| <u>A. HAZARDOUS</u> | | |
| Butyl benzyl phthalate | 85-68-7 | 5 - 10 % |
| DISTILLATES, PETROLEUM, HYDROTREATED | 64742-47-8 | 1 - 5 % |
| <u>B. NON-HAZARDOUS</u> | | |
| CALCIUM CARBONATE | 1317-65-3 | 30 - 60 % |
| Water | 7732-18-5 | 10 - 30 % |
| Vendor Trade Secret Acrylic polymer | - | 10 - 30 % |
| 2-Propenoic acid, Butyl ester,- Polymer with Ethenyl Acetate | 25067-01-0 | 1 - 5 % |

4. FIRST AID MEASURES

INGESTION

Do NOT induce vomiting. To avoid aspiration should vomiting occur, have the person lean forward. Get medical attention immediately. If victim is conscious, give 2-4 glasses of water. Never induce vomiting unless specifically directed by qualified medical personnel. Do not give victim anything to drink if he is unconscious.

SKIN

Flush skin with large amounts of water for at least 15 minutes until no evidence of chemical remains. Wash with soap and water.

PFC301WHT Acrylic Caulk

INHALATION

Move to fresh air. If not breathing, begin artificial respiration using a barrier device. Because of chemical properties, do not use mouth-to-mouth contact.

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

| | |
|---|-------------------|
| FLASH POINT: | > 93.3 °C; 200 °F |
| METHOD: | Estimated |
| IGNITION TEMPERATURE: | Not applicable |
| FLAMMABLE LIMITS IN AIR - LOWER (%): | Not applicable |
| FLAMMABLE LIMITS IN AIR - UPPER (%): | Not applicable |

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable. None

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section. Keep out of water supplies and sewers.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Use only in well-ventilated areas. Avoid accidental ingestion of this

Material Safety Data Sheet

Version: 1.1
06/03/2014

PFC301WHT Acrylic Caulk

material. Wash hands and face before eating, drinking, smoking, using toilet facilities, or applying cosmetics.

Keep container closed. Keep out of reach of children.

STORAGE

Store away from heat, sources of ignition, and incompatibles.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Showers; Eyewash stations; Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Neoprene

EYE AND FACE PROTECTION

Monogoggles; Safety glasses with side shields

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

| <u>Component</u> | <u>CAS RN</u> | <u>Source</u> | <u>Value</u> |
|------------------|---------------|---------------|--------------|
|------------------|---------------|---------------|--------------|

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F: Not applicable
VAPOR PRESSURE (20 C) (MM HG): Not applicable

PFC301WHT Acrylic Caulk

| | |
|--|--------------------|
| VAPOR DENSITY (AIR=1): | Not applicable |
| FREEZING POINT: | Not applicable |
| PHYSICAL STATE: | Solid |
| Color: | White |
| SPECIFIC GRAVITY (WATER=1): | 1.644 |
| ACID / ALKALINITY (MEQ/G): | Not applicable |
| SOLUBILITY IN WATER (20 C): | No data available. |
| SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT): | No data available. |
| VOLATILE ORGANIC CONTENT: | 1.4 %(m) |
| VOC EXCL. H2O & EXEMPTS (G/L): | 37.03 g/l |

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Hazardous polymerisation does not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide; Carbon Monoxide.; Nitrogen Oxides; Toxic monomer fumes.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

No data available.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: No data available.

ACUTE DERMAL

Remarks: No data available.

ACUTE INHALATION

Remarks: No data available.

OTHER

None.

SENSITIZATION

No data available.

PFC301WHT Acrylic Caulk

SKIN IRRITATION

No data available.

EYE IRRITATION

No data available.

MUTAGENICITY

No data available.

OTHER EFFECTS OF OVEREXPOSURE

This product contains butyl benzyl phthalate. Adverse reproductive effects have been reported in animals exposed to butyl benzyl phthalate through chronic feeding studies. Additionally, chronically fed rats exhibited leukemia and lymphomas, including Hodgkin's disease.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

Ecotoxicological data for this product is not available.

DISTRIBUTION

No data available.

CHEMICAL FATE

No data available.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

Australia Inventory of Chemical n (Negative listing)

PFC301WHT Acrylic Caulk

Substances (AICS)

Japan Inventory of Existing & New Chemical Substances (ENCS) n (Negative listing)

China Inventory of Existing Chemical Substances n (Negative listing)

Korea Existing Chemicals Inventory (KECI) n (Negative listing)

Canada DSL Inventory n (Negative listing)

Canada NDSL Inventory n (Negative listing)

Philippines Inventory of Chemicals and Chemical Substances (PICCS) n (Negative listing)

TSCA list y (positive listing) On TSCA Inventory

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

SARA (311,312) HAZARD CLASS

Acute Health Hazard; Chronic Health Hazard

SARA (313) CHEMICALS

75-21-8, Ethylene Oxide. 50-00-0, Formaldehyde. 79-06-1, Acrylamide. 108-05-4, Vinyl Acetate. 107-13-1, Acrylonitrile.

CALIFORNIA PROPOSITION 65

Warning! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

75-21-8, Ethylene Oxide. 50-00-0, Formaldehyde. 123-91-1, 1,4-Dioxane. 79-06-1, 2-Propenamide. 107-13-1, . 140-88-5, Ethyl Acrylate.

Canadian Regulatory Information

WHMIS HAZARD CLASS

D2B - Toxic Material Causing Other Toxic Effects

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

,C = ceiling limit NEGL = negligible

Material Safety Data Sheet

Version: 1.1
06/03/2014

PFC301WHT Acrylic Caulk

EST = estimated NF = none found
NA = not applicable UNKN = unknown
NE = none established REC = recommended
ND = none determined V = recommended by vendor
SKN = skin TS = trade secret
R = recommended MST = mist
NT = not tested STEL = short term exposure limit
ppm = parts per million ppb = parts per billion
By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).